

# Vyvolávací časy pro Foma R09

(ekvivalent Agfa Rodinal)

zdroj: <http://www.digitaltruth.com/devchart.php>

Film	ISO	Ředění	Čas	Teplota	
Delta 100 Pro	50	1+25	7	20°C	
	50	1+50	10	20°C	
	100	1+25	9	20°C	
	100	1+50	14	20°C	
	100	1+100	18	20°C	
	125	1+50	16	20°C	
	200	1+50	18	20°C	
Delta 3200 Pro	400	1+25	5,5	20°C	
	800	1+25	7	20°C	
	1000	1+25	8,5	20°C	
	1600	1+25	9	20°C	
	1600	1+63	28	20°C	
	3200	1+25	11	20°C	
	6400	1+25	20	20°C	
Delta 400 Pro	200	1+25	6,5	20°C	
	200	1+50	11	20°C	
	250	1+24	7,5	20°C	
	400	1+25	9	20°C	
	400	1+50	20	20°C	
	400	1+100	36	20°C	
	400	1+200	105	20°C	
	800	1+25	18,5	20°C	
	800	1+25	16	24°C	
	1600	1+16	20	20°C	
Eastman Double-X (5222)	25	1+100	3	20°C	
	200	1+20	5	20°C	
	200	1+60	7	20°C	
	250	1+25	5,75	20°C	
	250	1+50	11	20°C	
	400	1+50	11	20°C	
	800	1+50	18	18°C	
	1600	1+20	10	20°C	
	1600	1+300	480	20°C	
	800	1+50	13	20°C	
Fomapan T800	50	1+100	7	20°C	
	100	1+19	6,5	20°C	
	100	1+25	4	20°C	
	100	1+25	6,5	20°C	
	100	1+37	6,25	20°C	
	100	1+50	8-9	20°C	
	100	1+100	10	20°C	
	100	1+200	30	20°C	
	200	1+50	21,5	20°C	
	400	1+100	26	20°C	
Fomapan 200	200	1+25	5	20°C	
	200	1+50	8-10	20°C	
	400	1+50	14	20°C	
Fomapan 400	200	1+50	11	20°C	
	400	1+25	5,5	20°C	
	400	1+50	11	20°C	
	400	1+100	120	20°C	
	800	1+50	19	20°C	
	1600	1+50	24	20°C	
	3200	1+25	25	20°C	
3200	1+50	52	20°C		
FP4+	25	1+25	4	20°C	
	50	1+100	19	20°C	
	64	1+100	21	20°C	
	80	1+24	7,5	20°C	
	100	1+50	12	20°C	
	125	1+25	9	20°C	
	125	1+50	15	20°C	
	125	1+100	20	20°C	
	200	1+25	13	20°C	
	200	1+50	20	20°C	
	250	1+50	26	20°C	
	400	1+24	20	20°C	
	HP5+	25	1+50	7	20°C
		100	1+25	6	20°C
100		1+50	9	20°C	
160		1+100	20	20°C	
200		1+25	4,75	20°C	
200		1+25	5	20°C	
200		1+36	7,5	20°C	
200		1+50	10-13	20°C	
200		1+75	17	20°C	
250		1+50	12	24°C	
320		1+25	15	20°C	
400		1+25	6	20°C	
400		1+50	11	20°C	
400		1+50	7,25	24°C	
400		23+1000	13,5	20°C	
400		1+100	16	20°C	
400		1+100	80	21°C	
800		1+25	8	20°C	
800		1+50	16	20°C	
1600		1+25	12	20°C	
1600		1+50	24	20°C	
1600		1+100	120	20°C	
1600		1+200	240	20°C	
3200	1+25	18	21°C		
6400	1+50	52	20°C		

Film	ISO	Ředění	Čas	Teplota
Ilford Pan 100	100	1+25	9	20°C
	100	1+50	15	20°C
	200	1+25	13	20°C
	200	1+50	20	20°C
Ilford Pan 400	200	1+25	5	20°C
	200	1+50	9	20°C
	400	1+25	6	20°C
	400	1+50	11	20°C
	400	1+100	120	20°C
	400	1+100	35	20°C
Neopan 100 Acros	50	1+50	11	20°C
	64	1+50	10	20°C
	80	1+50	11,5	20°C
	100	1+25	6,5	20°C
	100	1+50	13,5	20°C
	100	1+50	8	24°C
Neopan 100ss	100	1+100	60	20°C
	100	1+100	18	20°C
	125	1+25	6,75	20°C
	400	1+25	7,75	20°C
	100	1+25	7-10	20°C
	100	1+50	14-16	20°C
Neopan 400	200-250	1+50	8-9	20°C
	200	1+100	15	20°C
	250	1+25	4,5	20°C
	250	1+100	20	20°C
	250	1+100	13	24°C
	400	1+25	6	20°C
	400	1+50	11	20°C
	800	1+25	7,5	22°C
	1600	1+25	10	20°C
	1600	1+60	90	20°C
Neopan 1600	200	1+25	3	20°C
	250	1+100	15	20°C
	320	1+49	5	20°C
	400	1+25	3,5	20°C
	400	1+100	20	20°C
	1600	1+25	5	20°C
	1600	1+50	8	20°C
Pan F+	25	1+100	15	20°C
	40	1+24	5	20°C
	50	1+19	5	20°C
	50	1+25	6	20°C
	50	1+50	11	20°C
	50	1+80	17	20°C
	50	1+100	60	20°C
	64	1+50	12	20°C
	80	1+50	13,5	20°C
	100	1+25	12	20°C
Plus-X	100	1+150	60	20°C
	64	1+100	10	20°C
	125	1+25	6	20°C
	125	1+50	13	20°C
Rollei Retro 100	200	1+85	12	24°C
	50	1+50	11,5	20°C
	64	1+24	7,5	20°C
	80	1+50	13	20°C
	100	1+50	13	20°C
	125	1+25	8	20°C
	160	1+25	9,5	20°C
Rollei Retro 400	160	1+50	17	20°C
	200	1+25	11	20°C
	200	1+50	21,5	20°C
	400	1+25	15	20°C
	400	1+50	29	20°C
	200	1+50	10	20°C
	200	1+100	15	20°C
	250	1+24	5	20°C
	250	1+49	8	20°C
	320-400	1+25	7	20°C
Surveillance 400 P4	320	1+25	10	20°C
	320	1+50	30	20°C
	320-500	1+50	11	20°C
	400	1+100	17	24°C
	800	1+25	14	20°C
	800	1+100	22	24°C
	125	1+50	10	20°C
	400	1+50	12	20°C
	400	1+50	14	20°C
	400	1+50	14	20°C
TMax P3200	1000	1+24	7	20°C
	1250-3200	1+25	8	20°C
	1250-3200	1+50	16	20°C
	6400	1+25	10,5	20°C
TMax 100	50	1+50	10	20°C
	50	1+75	17	20°C
	64-100	1+25	5,5-6	20°C
	64	1+100	15	20°C
	80-100	1+50	12	20°C
	80	1+100	20	20°C
	100	1+25	6	20°C
	100	1+75	19	20°C
	100	1+100	60	20°C
	400	1+25	8,5	20°C

Film	ISO	Ředění	Čas	Teplota
TMax 400	100	1+50	3,75	20°C
	160	1+100	20	20°C
	200	1+50	8	20°C
	200	1+100	60	20°C
	250	1+50	8,5	20°C
	320	1+25	5	20°C
	320	1+50	10	20°C
	400	1+25	6	20°C
	400	1+50	12	20°C
	400	1+80	16	21°C
	400	1+100	120	18°C
	640	1+300	150	21°C
	800	1+50	12	20°C
	800	1+100	24	20°C
	1600	1+25	11	20°C
	3200	1+25	17	20°C
Tri-X 320	200	1+25	7	20°C
	320	1+50	15	20°C
	320	1+100	20	20°C
Tri-X 400	100	1+50	7,5	20°C
	200	1+25	7	20°C
	200	1+50	9	20°C
	200	1+100	30	20°C
	250	1+100	15	20°C
	250	1+100	20	20°C
	320	1+24	6	20°C
	320	1+50	9,5	20°C
	400	1+25	7	20°C
	400	1+35	10	20°C
	400	1+50	13	20°C
	400	1+60	15	20°C
	400	1+75	17,5	20°C
	400	1+100	20	20°C
	400	1+100	24	21°C
	640	1+50	15,5	20°C
	800	1+50	16,5	20°C
	800	1+50	13	23°C
	800	1+100	17,5	24°C
	1600	1+50	18,5	20°C
	3200	1+50	33	20°C
3200	1+100	120	20°C	
12800	1+50	51	20°C	